



TF 400E TT Series with combined tilt & turning units

Turnable heavy-duty mast lighting systems with combined tilt & turning units

Teklite TF 400E TT lighting system with turnable air-operated telescopic mast, keyed mast sections, combined tilt and turning units, internal spiral cable and lamps either 12/24 volt powered by the vehicle battery or 110/230 volt generator powered.

The Teklite TF 400E TT series of mast lighting systems with combined tilt and turning units are especially designed for directional lighting applications where the mast and the angle of elevation of the floodlights can be remotely adjusted. Ideal for fitting to medium size or heavy fire vehicles.



MOBILE, PORTABLE & EMERGENCY LIGHTING

Mast specifications

Technical details



1 Mast top assembly with 4 x PG13,5 cable gland fitted to keyed mast sections

2 Standard natural clear anodised seamless drawn aluminium mast sections with 114 mm base tube

3 360° turnable cardan mast base with air connection, overpressure/drain valve and turning unit

4 Standard pre-mounted and connected warning switch

5 Mast top shroud to protect the keyed mast sections

6 Power supply cable (5 metres) with numbered wires for lamp/beacon/tilt unit connection

TF 400E TT Series mast models (Class II approved)

Model	Cat. No.	Retracted height	Extended height	Internal cable	Weight of mast
4 SECTION MASTS*					
TF 432E TT/4	34520	1230 mm	3140 mm	9 x 1.5 + 4 x 0.75 mm ²	21,0 kg
TF 440E TT/4	34521	1480 mm	4050 mm	9 x 1.5 + 4 x 0.75 mm ²	23,5 kg
TF 445E TT/4	34522	1660 mm	4700 mm	9 x 1.5 + 4 x 0.75 mm ²	25,5 kg
TF 453E TT/4	34523	1830 mm	5395 mm	9 x 1.5 + 4 x 0.75 mm ²	29,0 kg
TF 460E TT/4	34524	2030 mm	6000 mm	9 x 1.5 + 4 x 0.75 mm ²	31,0 kg
5 SECTION MASTS					
TF 432E TT/5	34530	1025 mm	3100 mm	9 x 1.5 + 4 x 0.75 mm ²	22,0 kg
TF 440E TT/5	34531	1275 mm	4000 mm	9 x 1.5 + 4 x 0.75 mm ²	24,0 kg
TF 445E TT/5	34532	1445 mm	4600 mm	9 x 1.5 + 4 x 0.75 mm ²	26,0 kg
TF 453E TT/5	34533	1670 mm	5300 mm	9 x 1.5 + 4 x 0.75 mm ²	30,0 kg
TF 460E TT/5	34534	1820 mm	5950 mm	9 x 1.5 + 4 x 0.75 mm ²	32,0 kg
TF 470E TT/5	34535	2000 mm	7000 mm	9 x 1.5 + 4 x 0.75 mm ²	33,0 kg

* All 4 section masts can be equipped with a S-STP/micro coax cable, suitable for video & audio applications.

Mast mounting

These mast fittings are available for mounting the mast inside or outside the body of the vehicle.

External mounting



Upper Mounting Bracket

Cat. No. 14049/SG



Lower Mounting Bracket

Cat. No. 14050/SG

Internal mounting



Roof Bearing

Cat. No. 14048/SG

Lamp choice

- * Lamp & tilt unit combination available with beacon & bracket (option). Put a "B" after the **tilt unit cat. no.** for ordering purposes.
- * Lamp & tilt unit combination available with lamp protection guard (option). Put a "P" after the **lamp unit cat. no.** for ordering purposes.

Double lamp unit, 2 lamps mounted on tilt unit

Cat. No.	Model	Volt	Ampere	Lumens
25273/T	2 x 70 Watt HP Sodium**	12	12,5	13.000
25274/T	2 x 70 Watt HP Sodium**	24	7,0	13.000
25275/T	2 x 70 Watt Metal Halide**	12	13,0	10.000
25276/T	2 x 70 Watt Metal Halide**	24	7,4	10.000
27280/T	1 x 70 Watt HPS + 1 x 70 Watt MH**	12	12,8	11.500
27285/T	1 x 70 Watt HPS + 1 x 70 Watt MH**	24	7,2	11.500
27290/T	2 x 35 Watt Xenon*	12	5,9	7.000
25268/T	2 x 35 Watt Xenon*	24	3,0	7.000
25277/T	2 x 100 Watt Xenophot**	12	16,7	7.200
25278/T	2 x 150 Watt Xenophot**	24	12,5	12.000
27295/T	2 x 200 Watt Xenophot**	12	33,4	14.400
27300/T	2 x 300 Watt Xenophot**	24	25,0	24.000
25279/T	2 x 500 Watt Halogen**	230	4,4	19.000
27301/T	2 x 750 Watt Halogen**	230	6,5	33.000
25280/T	2 x 1000 Watt Halogen**	230	8,7	44.000
25860/T	2 x 1500 Watt Halogen**	230	13,0	72.000
25108/T	2 x 250 Watt HP Sodium*	24	23,0	54.000
27315/T	2 x 400 Watt HP Sodium**	230	9,0	110.000
27320/T	2 x 400 Watt Metal Halide**	230	9,0	66.000
27325/T	1 x 400 Watt HPS + 1 x 400 Watt MH**	230	9,0	88.000
35911/T	2 x 55 Watt SMD-LED**	12	10,6	11.000
35916/T	2 x 55 Watt SMD-LED**	24	4,8	11.000



Quadruple lamp unit, 4 lamps mounted on tilt unit

Cat. No.	Model	Volt	Ampere	Lumens
27330/T	4 x 70 Watt HP Sodium*	12	25,0	26.000
27335/T	4 x 70 Watt HP Sodium**	24	14,0	26.000
27340/T	4 x 70 Watt Metal Halide*	12	26,0	20.000
27345/T	4 x 70 Watt Metal Halide**	24	14,8	20.000
27350/T	2 x 70 Watt HPS + 2 x 70 Watt MH*	12	25,6	23.000
27355/T	2 x 70 Watt HPS + 2 x 70 Watt MH**	24	14,4	23.000
27360/T	4 x 35 Watt Xenon* + Converter	12	11,7	14.000
25269/T	4 x 35 Watt Xenon*	24	5,9	14.000
25515/T	4 x 100 Watt Xenophot**	12	33,4	14.400
25281/T	4 x 150 Watt Xenophot**	24	25,0	24.000
27365/T	4 x 300 Watt Xenophot*	24	50,0	48.000
25282/T	4 x 500 Watt Halogen**	230	8,7	38.000
27366/T	4 x 750 Watt Halogen**	230	13,0	66.000
25283/T	4 x 1000 Watt Halogen**	230	17,4	88.000
25861/T	4 x 1500 Watt Halogen**	230	26,2	144.000
27375/T	4 x 250 Watt HP Sodium	24	46,0	108.000
27380/T	4 x 400 Watt HP Sodium**	230	18,0	220.000
27385/T	4 x 400 Watt Metal Halide**	230	18,0	132.000
27390/T	2 x 400 Watt HPS + 2 x 400 Watt MH**	230	18,0	176.000
35921/T	4 x 55 Watt SMD-LED**	12	21,2	22.000
35926/T	4 x 55 Watt SMD-LED**	24	9,6	22.000



Hexuple lamp unit, 6 lamps mounted on tilt unit

Cat. No.	Model	Volt	Ampere	Lumens
33425/T	6 x 35 Watt Xenon*	24	9,0	21.000
33435/T	6 x 500 Watt Halogen**	230	13,0	57.000
33440/T	6 x 750 Watt Halogen**	230	19,6	99.000
33445/T	6 x 1000 Watt Halogen**	230	26,0	132.000
35931/T	6 x 55 Watt SMD-LED**	12	31,8	33.000
35936/T	6 x 55 Watt SMD-LED**	24	14,4	33.000

Air supply for mast extension

The air pressure for mast extension may be provided by a battery powered compressor or from the vehicle air pressure system.

Using the vehicle battery power



“TekAir” Compressor Model 40/50

IMPORTANT NOTE :
All our compressors are supplied with a NO (normal open) valve. They need permanent current during operation of the mast lighting system. However, when there are applications where there is no permanent current available (e.g. mast fitted to a standalone container), apply for a compressor with a NC valve.

Models with NO Valve

“TekAir” Compressor Model 40/50, 12 volt	Cat. No. 33640
“TekAir” Compressor Model 40/50, 24 volt	Cat. No. 33642

Models with NO Valve and Deadman Function

“TekAir” Compressor Model 40/50, 12 volt	Cat. No. 33641
“TekAir” Compressor Model 40/50, 24 volt	Cat. No. 33643



Remote Control for “TekAir” Compressor Model 40/50

The complete remote control set is delivered with 5 metre cable and connection plug.

Models

Model 12 volt	Cat. No. 25798
Model 24 volt	Cat. No. 25799

Models with Deadman Function

Model 12 volt	Cat. No. 25220
Model 24 volt	Cat. No. 25221

Using the vehicle air pressure system



Air Pressure Control Unit

Combined unit consisting of manometer, pressure regulator and control handle.

Models

AP Control Unit	Cat. No. 25218
AP Control Unit with Deadman Function	Cat. No. 25219

Combined Tilt & Turning Units with remote control



Horizontal Tilt Unit Models

Model 12 volt	Cat. No. 27409
Model 24 volt	Cat. No. 27410

Tilting angle : 110°



Vertical Tilt Unit Models

Model 12 volt	Cat. No. 27411
Model 24 volt	Cat. No. 27412

Tilting angle : 110°



Turning Unit Models

Model 12 volt	Cat. No. 27417
Model 24 volt	Cat. No. 27418

Rotation : 360°



Tilt & Turning Units Remote Control

Model 12/24 volt	Cat. No. 27421
------------------	----------------

NOTE :

Combined remote control for compressor, tilt & turning units is available on request.



All details given in this publication are approximate and may be subject to change without notice.

Distributor :

TEKSAM COMPANY NV, Woudstraat 21, 3600 Genk, Belgium

Tel : +32 (0)89 38 44 72 Fax : +32 (0)89 38 61 41 E-mail : info@teksamco.com Website : www.teklite.com

TEKLITE is a division of Teksam Company NV

ISO 9001:2008 CE