

ACsf/fx

THE FUTURE OF SCBA



THE LIGHTEST SCBA. IN IT'S CLASS.

THE FUTURE OF SCBA.

Scott Safety's ACS represents a major advancement in SCBA. It is significantly lighter than any other carrying system and offers the wearer the ultimate in comfort and flexibility. The result is considerably reduced user burden combined with the highest standards of performance.



- For over 75 years Scott Safety's innovative engineering and customer led product evolution has enabled their range of Breathing Apparatus to adapt, respond and predict the ever changing needs of professional fire services.
Today over one million firefighters worldwide trust in its high performance, rugged dependability and cutting edge technology. Backed by dedicated customer support, Scott Safety's SCBA is the firefighters preferred choice.
Approved to EN137: 2006 Class II, incorporating the stringent Flame Engulfment Test, ACSf and ACSfx are refined to a unequalled level of performance and user comfort for the professional firefighter.
- **REDUCED USER BURDEN**
 - ACS is the lightest carrying system in its class. It is significantly lighter than competitor products, increasing comfort, ease of movement and reducing firefighter fatigue.
- **LOWER THROUGH LIFE COSTS / EASY UPGRADE PATH**
 - All components are user serviceable, low cost and easy to maintain.
 - All elements of the set are designed to allow future upgrade with minimal cost.
- **EASY DECONTAMINATION**
 - Both the back plate and harness can be washed with your turnout gear.
 - The new material used is approved to maintain its flame retardant qualities when washed following the care and instructions at 30°C.
- **RANGE OF SPECIFICATIONS**
 - ACSf is a Class II, high performance Breathing Apparatus set with an extensive range of benefits for the modern firefighter.
 - ACSfx provides all the features of the ACSf but also has an adjustable waist belt that can be adjusted to suit the height of the wearer.
- **HIGH PERFORMANCE PNEUMATICS**
 - Supplies exceptionally high airflow, simple to maintain and fully user serviceable.
 - No tools are necessary to remove the pneumatics, simply rotate the pneumatics 90 degrees mounting.
- **WIDE RANGE OF SPECIFICATIONS**
 - Wide choice of facemasks including Vision 3 and Promask PP ranges.
 - ACSf and ACSfx are approved with a wide range of cylinders.
 - ACSf and ACSfx are approved with a variety of valve styles.



MAJOR COMPONENTS

Compact positive pressure demand valve featuring servo-assisted, tilting diaphragm mechanism with low inspiratory resistance and responsive dynamic performance, automatic first breath actuation and hands free bypass facility.

REDUCING VALVE

First stage pressure reducing valve featuring non-adjustable, spring loaded piston mechanism and outlet supply protected by pressure relief valve.

PRESSURE INDICATOR & WARNING WHISTLE

Bourdon tube type dial indicator
Heat and Impact resistant polycarbonate lens

HOSES

Stainless steel swivel hose fittings
Medium pressure hose
Maximum working pressure 16 bar
Minimum burst pressure 80 bar
High pressure hose
Maximum working pressure 450 bar
Minimum burst pressure 800 bar

COMMUNICATIONS

Sabre-Com is a unique radio communications interface that fully integrates with your existing radio and preferred choice of Scott facemask. Sabre-Com is intrinsically safe and approved to EN136 Class 3.

OPTIONS

Scott ACS can be specified in many configurations including Duo, Split Demand Valve Coupling (SDC) and attachments for Airline, which can also be used for Rescue Second Man (RSM) and Decontamination.



Adjustable padded shoulder straps

Reflective thread for extra visibility

Rapid connect cylinder band allows adjustment or change out of cylinder in seconds

Ergonomically moulded to fit spine and back muscles, designed in conjunction with an osteopath

Quick pull forward action allows easy in-transit adjustment of shoulder straps

Swivelling waistbelt

50% Kevlar Pyrogard blend webbing with wrap-around harnesses

Lightweight ThermoFlex backplate for greater comfort, flexibility and reduced wearer fatigue

Adjustable waistband featuring large buckles for easy operation with gloved hands and fast donning and doffing

Extendable backplate (ACSfx only)

PNEUMATIC SYSTEM

At the heart of the ACS set is a simple and reliable two-stage pneumatic system. A first breath activated positive pressure demand valve provides low breathing resistance and excellent dynamic performance - particularly at high flow rates. A first stage pressure reducing valve features only two moving parts and accepts cylinders pressures of up to 300 bar without adjustment.





The lightest SCBA in its class.

Approved to EN137: 2006 Class II, incorporating the stringent Flame Engulfment Test, ACSf and ACSfx are refined to a unequalled level of performance and user comfort for the professional firefighter.

SPECIFICATIONS & ORDERING INFORMATION

ACSf/fx SELF CONTAINED BREATHING APPARATUS

Product Specifications

Weight

Single configuration (less cylinder)
ACSf 3.08kg ACSfx 3.10kg

Single configuration & Facemask (less cylinder)
ACSf 3.70kg ACSfx 3.72kg

Duo configuration with manifold
and facemask (less cylinder)
ACSf 4.22kg ACSfx 4.24kg

Dimensions

Length 565mm (ACSfx extends up to 610mm)
Width 260mm
Depth (with 6.8 litre 300 bar Cylinder) 245mm

ACS		
Part Number	Description	Application
ACSf	EN137 Approved, Class II	Fire
ACSfx	EN137 Approved, Class II, Extendable length	Fire

Approvals:

ACSf/fx EN137:2006 Class II Fire Fighting sets, ACSm/i EN137:2006 Class I apparatus, Australian Standard AS1716, MED (Shipwheel Approved)



Scott Safety is a global business unit of Tyco International that supplies a variety of industries through manufacturing facilities located in the United States, United Kingdom, Asia, Finland and Australia.
Pimbo Road • Skelmersdale • Lancashire • England • WN8 9RA Telephone: +44 (0) 1695 711711 • Fax: +44 (0) 1695 711772
www.scottsafety.com • scott.sales.uk@tycointl.com