

# PROPAK-F

*HIGH PERFORMANCE, RUGGED DEPENDABILITY, TRUSTED TECHNOLOGY*



The ProPak-F has been designed for use by the Fire Service or as a fire fighting set in the Oil & Gas fire fighting market.

The entire ProPak range has been approved to EN137:2006 Type 2, incorporating the stringent Full Flame Engulfment Test, and to the 9th amendment of the MED meaning that it has the latest approval for the Marine industry.

## **PRODUCT HIGHLIGHTS**

---

- EN137:2006 Type 2, MED Approved Breathing Apparatus
- Designed for use by the Fire Service or the Oil & Gas market
- Rigid backframe construction
- Easily removable pneumatics
- Simple to service and maintain

# PROPAK-F

## SELF CONTAINED BREATHING APPARATUS



Quick pull forward action allows easy in-transit adjustment of shoulder strap

Adjustable, padded shoulder straps

Kevlar & Pyrogard blend wrap around harness

Reflective webbing

Side arms for increased user comfort

Waistband featuring large buckles for easy operation with gloved hands and fast donning and doffing

### MAJOR COMPONENTS

Compact positive pressure demand valve featuring servo-assisted, tilting diaphragm mechanism with low inspiratory resistance and responsive dynamic performance, automatic first breath actuation and hands free bypass facility

### REDUCING VALVE

First stage pressure reducing valve featuring non-adjustable, spring loaded piston mechanism and outlet supply protected by pressure relief valve

### HOSES

Stainless steel swivel hose fittings  
 Medium pressure hose  
 High pressure hose  
 Medium working pressure 16 bar  
 Minimum burst pressure 80 bar  
 Maximum working pressure 450 bar  
 Minimum burst pressure 800 bar

### PRESSURE INDICATOR & WARNING WHISTLE

Bourdon tube type dial indicator  
 Heat and Impact resistant polycarbonate lens

### COMMUNICATIONS

The Sabrecom2 is a radio communication interface designed for use with Scott Safety's range of positive pressure full facemasks. Fully integrated and ready to use the Sabrecom 2 is approved to EN136 class 3, meeting the stringent flame and radiant heat test requirements.

### OPTIONS

The Scott Safety ProPak-f can be specified in many configurations including Duo, Split Demand Valve Coupling (SDC), Y-Piece (Y2C) and attachments for Airline, which can be used for Rescue Second Man and Decontamination. Cylinder quick connect and fast fill options are also available.



Product Specifications		
<b>Weight</b>		
Single Configuration (less cylinder)		3.2kg
Single Configuration and facemask (less cylinder)		3.8kg
<b>Dimensions</b>		
Length		630mm
Width		285mm
Depth (with a 6 litre 200 bar cylinder)		220mm
Ordering Information		
Part Number	Description	Application
ProPak-f	EN137 Approved, Type 2	Fire Service/Oil & Gas Fire Fighting



Scott Safety is a global business unit of Tyco International that supplies a variety of industries through manufacturing facilities located in the United States, United Kingdom, Asia, Finland and Australia.

Pimbo Road • Skelmersdale • Lancashire • England • WN8 9RA Telephone: +44 (0) 1695 711711 • Fax: +44 (0) 1695 711772  
 www.scottsafety.com • scott.sales.uk@tycointl.com

© 2012 Scott Safety. SCOTT, the SCOTT SAFETY Logo, Scott Health and Safety, ProPak-f are registered and/or unregistered marks of Scott Technologies, Inc. or its affiliates.

