# **PROPAK-FX**

HIGH PERFORMANCE, RUGGED DEPENDABILITY, TRUSTED TECHNOLOGY



The ProPak-FX has been designed specifically to meet the demands of the Professional Fire Service offering an unequalled level of performance and user comfort through the adjustable backplate.

The entire ProPak range has been approved to EN137:2006 Type 2, incorporating the stringent Full Flame Engulfment Test, and to the 9th amendment of the MED meaning that it has the latest approval for the Marine industry.

### **PRODUCT HIGHLIGHTS**

- EN137:2006 Type 2 MED Approved Breathing Apparatus
- Designed specifically for use by the Professional Fire Service
- Rigid backframe construction with adjustable backplate
- Easily removable pneumatics
- Simple to service and maintain



## **PROPAK-FX**

#### SELF CONTAINED BREATHING APPARATUS



#### MAJOR COMPONENTS

Compact positive pressure demand valve featuring servo-assisted, tilting diaphragm mechanism with low inspiratory resistance and responsive dynamic performance, automatic first breath actuation and hands free bypass facility

#### **REDUCING VALVE**

First stage pressure reducing valve featuring non-adjustable, spring loaded piston mechanism and outlet supply protected by pressure relief valve

#### HOSES

Stainless steel swivel hose fittings Medium pressure hose High pressure hose Medium working pressure 16 bar Minimum burst pressure 80 bar Maximum working pressure 450 bar Minimum burst pressure 800 bar

#### The Sabrecom2 is a radio communication interface designed for use with Scott Safety's range of positive pressure full facemasks. Fully integrated and ready to use the Sabrecom 2 is approved to ENI36 class 3, meeting the stringent flame and radiant heat test requirements. OPTIONS

The Scott Safety ProPak-FX can be specified in many configurations including Duo, Split Demand Valve Coupling (SDC), Y-Piece (Y2C) and attachments for Airline, which can be used for Rescue Second Man and Decontamination. Cylinder quick connect and fast fill options are also available.

**PRESSURE INDICATOR & WARNING WHISTLE** 

Heat and Impact resistant polycarbonate lens

Bourdon tube type dial indicator

COMMUNICATIONS

Product Specifications		
Weight		
Single Configuration (less cylinder)		3.4kg
Single Configuration and facemask (less cylinder)		) 4.0kg
Dimensions		
Length		630mm
Width		285mm
Depth (with a 6 litre 200 bar cylinder)		220mm
Ordering Information		
Part Number	Description	Application
ProPak-FX	EN137 Approved, Type 2	Professional Fire Service



Scott Safety is a global business unit of Tyco International that supplies a variety of industries through manufacturing facilities located in the United States, United Kingdom, Asia, Finland and Australia.

Pimbo Road • Skelmersdale • Lancashire • England • WN8 9RA Telephone: +44 (0) 1695 711711 • Fax: +44 (0) 1695 711772 www.scottsafety.com • scott.sales.uk@tycoint.com





