

PROPAK-I

HIGH PERFORMANCE, RUGGED DEPENDABILITY, TRUSTED TECHNOLOGY



The ProPak-i has been designed for use as a fire fighting set in the Industrial, Professional Fire Fighting or Oil & Gas markets.

The entire ProPak range has been approved to EN137:2006 Type 2, incorporating the stringent Full Flame Engulfment Test, and to the 9th amendment of the MED meaning that it has the latest approval for the Marine industry.

PRODUCT HIGHLIGHTS

- EN137:2006 Type 2 MED Approved Breathing Apparatus
- Compliance set for Industrial Professional Fire Fighting or Oil & Gas markets
- Rigid backframe construction
- Easily removable pneumatics
- Simple to service and maintain

PROPAK-I

SELF CONTAINED BREATHING APPARATUS



MAJOR COMPONENTS

Compact positive pressure demand valve featuring servo-assisted, tilting diaphragm mechanism with low inspiratory resistance and responsive dynamic performance, automatic first breath actuation and hands free bypass facility

REDUCING VALVE

First stage pressure reducing valve featuring non-adjustable, spring loaded piston mechanism and outlet supply protected by pressure relief valve

HOSES

Stainless steel swivel hose fittings
 Medium pressure hose
 High pressure hose
 Medium working pressure 16 bar
 Minimum burst pressure 80 bar
 Maximum working pressure 450 bar
 Minimum burst pressure 800 bar

PRESSURE INDICATOR & WARNING WHISTLE

Bourdon tube type dial indicator
 Heat and Impact resistant polycarbonate lens

COMMUNICATIONS

The Sabrecom2 is a radio communication interface designed for use with Scott Safety's range of positive pressure full facemasks. Fully integrated and ready to use the Sabrecom 2 is approved to EN136 class 3, meeting the stringent flame and radiant heat test requirements.

OPTIONS

The Scott Safety ProPak-i can be specified in many configurations including Split Demand Valve Coupling (SDC), Y-Piece (Y2C) and attachments for Airline, which can be used for Rescue Second Man and Decontamination.



Product Specifications		
Weight		
Single Configuration (less cylinder)	2.9kg	
Single Configuration and facemask (less cylinder)	3.5kg	
Dimensions		
Length	630mm	
Width	285mm	
Depth (with a 6 litre 200 bar cylinder)	220mm	
Ordering Information		
Part Number	Description	Application
ProPak-I	EN137 Approved, Type 2	Industrial/Oil & Gas Fire Fighting



Scott Safety is a global business unit of Tyco International that supplies a variety of industries through manufacturing facilities located in the United States, United Kingdom, Asia, Finland and Australia.

Pimbo Road • Skelmersdale • Lancashire • England • WN8 9RA Telephone: +44 (0) 1695 711711 • Fax: +44 (0) 1695 711772
 www.scottsafety.com • scott.sales.uk@tycointl.com

