





TRELLCHEM® VPS



Trellchem® VPS type CV with sewn-in socks/booties and separate boots.

Provides maximum protection against hazardous chemicals in liquid, vapor, gaseous and solid form, including warfare agents. Trellchem® VPS is certified to the European standards EN 943-1 and EN 943-2/ET.

GARMENT MATERIAL

The combination of elastomers and plastics with a woven fabric makes a strong and flexible material that offers an outstanding chemical barrier - more than 8 hours protection against a wide range of chemicals - coupled with an excellent resistance to abrasion, provided by the outer layer of chloroprene rubber.

COLOR

Yellow.

STANDARDS

- EN 943-1 and EN 943-2/ET
- EN 1073-2 (radioactive particles)
- EN 14126 (infective agents)
- SOLAS



RELLCHE

THE SAFETY STANDARD


TRELLCHEM® VPS



Type VP1



Туре Т



Trellchem® seam

Ansell Protective Solutions AB

Johan Kocksgatan 10, SE-231 81 Trelleborg, Sweden Tel: +46 10 205 1800, Fax: +46 10 205 1840 http://protective.ansell.com | order.protective@ansell.com

DESIGN

Trellchem® VPS comes in different designs to fit all user preferences:

- Encapsulating design with hump (type CV or VP1), BA worn inside the suit, or
- Non-encapsulating design with face seal and without hump (type T), BA worn outside the suit.

VISOR/FACE SEAL

The visor on encapsulating suits is made from a rigid 2 mm impact and chemical resistant PVC. Option of two visors; CV or the larger VP1. Non-encapsulating suits are fitted with an anatomically designed face seal.

ZIPPER

Strong and durable gastight chloroprene rubber coated zipper. Closing downwards for added safety. The zipper is protected by a splash guard (flap).

Note: EN 943-2/ET certified suits are equipped with the Trellchem® HCR zipper.

VENTILATION

A ventilation system is included as standard. For the safety of the wearer it provides a constant level of overpressure inside the suit. The Trellchem® regulating valve has 3 ventilation rates (2, 30 and 100 l/min) plus zero/off position and is also available in a passthrough version for use with external air supply.

GLOVES & ATTACHMENTS

The standard glove assembly consists of two layers:

- Inner Ansell Barrier® glove
- Outer glove made of flame retardant chloroprene rubber, or the Trellchem® Viton®/butyl rubber glove (ET suits)

The gloves are attached with the Trellchem® Bayonet glove ring system, which offers quick and simple glove exchange.

FOOTWEAR & ATTACHMENTS

Black nitrile rubber safety boots with European approval as Firemen's boots. Alternatively the suit has a sewn-on sock/bootie in the suit material.

SEAM

Stitched with aramid thread for superior strength and durability. Taped with a rubber strip on the outside and a barrier laminate strip welded to the inside. This provides a continuous barrier layer across the seam.

Trellchem* is a registered trademark owned by Trelleborg. Viton* is a registered trademark owned by DuPont Perfomance Elastomers L.L.C. ©2013 Ansell Limited. All Rights Reserved.

