

Selectable Gallonage Nozzle

Style 368

- Combination pattern nozzle with versatile multiple flow settings
- Produces straight stream for maximum reach and superb wide fog pattern for optimum fire fighter protection
- Lightweight hardcoat anodized aluminium construction
- Available in tip only and shutoff/playpipe combinations
- Standard operating pressure at 100 psi (7bar), optional 85 psi (6 bar) or 75 psi (5 bar)
- Minimal maintenance reflected in robust design, precision machining and quality materials
- Standard NH inlet or optional BIM / Machino / Storz inlets
- Compatible with Protek's foam aeration tubes
- Conforms to all aspects of NFPA 1964 (Spray Nozzles, Shutoffs and Tips)



Raised lug for flashover fog pattern



Newly improved handle with two reinforced pieces on each side to prevent breakage



Specification

Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
368	2-1/2" (65mm)	11" (279mm)	6.3 (2.8kg)	95-125-150-200-250	360-475-550-750-950



Selectable Gallonage Nozzle

Style 368

Unique Features On Protek Nozzles



Technical Data

Style	Nozzle Pressure		Flow Setting		Actual Flow		Straight Stream Reach			
	PSI	BAR	GPM	LPM	GPM	LPM	Effective		Overall	
							Feet	Meters	Feet	Meters
368	75	5	95	360	82	310	115	35	125	38
			125	475	108	409	125	38	135	41
			150	550	130	492	145	44	155	47
			200	750	173	654	155	47	165	50
			250	950	217	821	160	48	170	51
	100	7	95	360	95	360	140	42	150	45
			125	475	125	475	150	45	160	48
			150	550	150	550	160	48	170	51
			200	750	200	750	170	51	180	54
			250	950	250	950	175	53	185	56
	125	8.5	95	360	106	401	145	44	155	47
			125	475	140	530	155	47	165	50
150			550	168	636	160	48	170	51	
200			750	224	848	175	53	185	56	
250			950	280	1060	185	56	195	59	

