

Powder Fire Extinguisher On Trolley EN 1866

PRESSURE EQUIPMENT DIRECTIVE
APPROVED FIRE EXTINGUISHERS

MARINE EQUIPMENT DIRECTIVE
APPROVED FIRE EXTINGUISHERS

BRITISH STANDARDS INSTITUTION



0029



0029



PENDING



- SRIABC dry chemical powder fire extinguisher on trolley is effective for use on class A, B & C fire and it is ideal for multi-risk fire.
- Trolley unit can be operated by one person and suitable for areas with high risk fire such as industrial facilities.

STORE PRESSURE TYPE			CARTRIDGE TYPE	
CODE NO.	FEX220-MS-250-EN	FEX221-MS-500-EN	FEX225-MS-250-EN	FEX222-MS-500-EN
CAPACITY	25kg	50kg	25kg	50kg
PROPELLANT	Nitrogen	Nitrogen	0.28kg Nitrogen Cartridge	0.86kg Nitrogen Cartridge
FIRE RATING	A II B C	A II B C	A II B C	A II B C
OPERATING TEMPERATURE	-30°C to 60°C	-30°C to 60°C	-30°C to 60°C	-30°C to 60°C
OPERATING PRESSURE	14bar	14bar	14bar	14bar
TEST PRESSURE	25bar	25bar	25bar	25bar
APPROX. FULL WEIGHT	55kg	95kg	60kg	106kg
APPROX. SIZE (WxLxH mm)	460x550x940	560x700x1020	460x550x940	560x750x1026
APPROX. DISCHARGE TIME	18-25 secs	33-40 secs	16-24 secs	43-57 secs
APPROX. THROW RANGE	10m	10m	10m	10m

Optional: Other capacity are available upon request.