



**THE WORLDWIDE
DIVING STANDARD**

VIKING™ SRS (SURFACE RESCUE SUIT)



Viking SRS in Nylon/Butyl/Nylon material (inset shows the same suit with red top).

Provides protection for users such as fire rescue teams, coastguard, environment agency teams and other water borne personnel who are not divers, but are working on, near or above water. Ideal for shallow water wading operations.

- Lightweight flexible materials.
- "Vulca Seam technology" ensures watertight seams for the life of the suit.
- Protects the wearer from water borne biological contaminants
- Easy to clean biological contamination from surface
- Front entry adjustable torso for operational comfort

SUIT MATERIAL

Two material options are available as follows:

- **450 g/m²** Cordura textured outer/Butyl midply/Polyester inner. Light and strong with good puncture and abrasion resistance.
- **350 g/m²** Nylon outer/Butyl midply/Nylon inner. Lighter and more flexible than Cordura, but with equally good puncture and abrasion resistance. Smooth close knit exterior surface.

SEAMS

External seams are stitched together with an elastic tape for security. Internal seams are chemically treated and then an uncured rubber tape is applied to the seams using heat and pressure. Finally the suit is placed inside a vulcanizer whereby the rubber tape becomes cured into the material surface. This is known as "Vulca Seam technology".

COLOR

Black legs with black top / Black legs with yellow top / Black legs with red top.

SOLAS reflectors are fitted as standard to the front and back of wrists, upper arms and backs of legs for visibility.



THE WORLDWIDE
DIVING STANDARD

VIKING™ SRS (SURFACE RESCUE SUIT)



SIZE RANGE

- Viking Regular: 00/SML, 01/MED, 02/LGE, 03/EXL, 04/XXL
- Viking Wide: 00/SML, 01/MED, 02/LGE, 03/EXL, 04/XXL
- Viking Double Wide: 00/SML, 01/MED, 02/LGE, 03/EXL, 04/XXL

See the Viking size chart for detailed size measurements along with boot sizing.

REINFORCEMENTS

The Viking SRS material is inherently abrasion and puncture resistant. Shaped "Superfabric" knee pads featuring flexible cut and abrasion resistant guard plates are fitted to the legs above and below the knees.

ZIPPER

A medium duty non-mag zipper (85 cm or 90 cm length dependent on suit size) is placed across the upper body. Zipper flap fitted as standard.

NECK SEAL

The Viking SRS is fitted with a Bellows latex neck seal as standard. Option: Viking Quick Connect Collar system which allows for quick changing of broken seals. A neoprene neck warmer may be paired with a latex neck seal.

HOOD OPTIONS

Viking SRS suits may be fitted with a wide range of hood options as follows: Surveyor latex hood + thermal inner hood, Nautic neoprene hood with smooth face seal or Smoothskin hood.

CUFFS

Latex conical cuffs are the standard fitment. Alternatively the suit can be fitted with a rubber cuff ring system or the Viking Bayonet Ring System. Both systems make the fitment of latex gloves possible.

FOOTWEAR

Rubber coated 5 mm neoprene boots are fitted as standard. Alternative boot options are available.

INCLUDED WITH EACH DELIVERY

Each suit comes supplied with suspenders, carry bag, user manual, repair kit and zip care materials.

CERTIFICATION & APPROVALS

- PPE Directive 89/686/EEC using applicable parts of EN 15027-1

* & ™ are trademarks owned by Ansell Limited or one of its affiliates. © 2013 Ansell Limited. All Rights Reserved.