

**HARVIK**

FIREFIGHTING BOOTS

with 18kV ESR Protection

When you're in the line of fire...

WORLD-CLASS PERFORMANCE IS ESSENTIAL

Handmade precisely under stringent condition keeping into consideration the needs and requirements of firefighter boots standards. Every pair of firefighter boot is thoroughly checked and is according to the requirement international standards.

Product Features :

- EN 15090:2006, EN ISO 20345:2004, CSA Z195-02 / ASTM F 2413-05
- Flame Retardant Upper
- High Contrast Colours for Good Visibility
- Steel Toe Cap and Steel Midsole Protection
- Heat and Oil Resistant Anti-Slip Sole
- Ozone Resistant Upper
- Heel Energy Absorbing Sole Construction
- Heavy Canvas Lining for Extra Comfort
- Electric Shock Resistant Outsole up to 18kV
- Sponge Cushion Insole
- Extra Padding for Ankle, Heel Tendon and Shin Protection
- Heat and Cold Insulating Outsole
- Mild Acid and Alkaline Resistant Upper
- Pull-up Strap for Easy Don and Doff



ARTICLE
9687L

Harvik Rubber Industries Sdn Bhd (12096-P)

No. 1414, Lorong Perusahaan 4, Free Industrial Zone (1),
13600 Prai, Penang, Malaysia.






Tel : +604-390 7550

Fax: +604-390 8570

Email: harvik@harvik.com

Url : www.harvik.com



Colour	Black / Yellow
Size Range	Euro:36 - 50 UK :3½ - 14½ US :4½ - 15½
Type of construction	Vulcanized Rubber Upper and Sole
Last / Sole Pattern	VSV / NJV
Recommendation	<ul style="list-style-type: none"> • Structural fire fighting • General fire rescue • Bush fire fighting
Compliance    AS/NZS 4821 : 2006 PETIHI  	<p>European Standard CE Approved - EN 15090 : 2006 (F2 IS HI3 P T CI) EN ISO 20345 : 2004 (SB P E CI SRA)</p> <p>Australia New Zealand Standard Approved - AS/NZS 4821 : 2006 (P E T I HI)</p> <p>F2 = Type 2 footwear for firefighters suitable for fire rescue, fire suppression, property conservation & etc. SB = Standard Basic Protection as per EN ISO 20345 IS = High Electrical Resistance Outsole HI₃ = Heat Insulation Level 3 CI = Cold Insulation SRA = Slip Resistance on ceramic tile with Sodium Lauryl Sulphate E = Heel Energy Absorption P = Penetration Resistance T = Toe Protection HRO = Resistant to heat contact</p> <p>CSA Z195-02 / ASTM F 2413-05 Grade 1 Toe protection Penetration resistance 18 kV Electric Shock Resistance (ESR) protection</p>
Lining Material	<ul style="list-style-type: none"> • Extra comfort with woven cotton canvas
Upper Construction	<ul style="list-style-type: none"> • Flame retardant upper with heat insulation • Reinforced rubber upper • Waterproof • High visibility with black and yellow contrast
Sole / Heel	<ul style="list-style-type: none"> • Flame retardant rubber outsole • Fuel oil resistant sole suitable for inimical environment • Slip resistant vulcanized rubber outsole • Excellent abrasion resistant for extra durability • Withstand 18kV of life current at dry condition • Heel energy absorption design to minimize heel impact • Catered to enter high temperature • Cold insulation sole construction
Steel Midsole	<ul style="list-style-type: none"> • Non-corrosive stainless steel • Withstands pin & sharp objects
Steel Toe Cap	<ul style="list-style-type: none"> • Epoxy coated toe caps • Meets EN ISO 20345 impact and compression tests • Reliable protection in cold & hot environment
Chemical Resistance	<ul style="list-style-type: none"> • Sole & Upper - Resistant towards mild acids and alkalines
Finishing	<ul style="list-style-type: none"> • Lacquer coating for weather protection
Packing	<ul style="list-style-type: none"> • Recyclable Polybag & 6 pairs in a carton

*Specifications of the product are subject to changes without prior notice for further enhancements.