

## CL - Compact Line KLF, Small fire truck



In accordance with ÖBFV-RL FA-02 and EN 1846 / Unterthal-Rohrmoos Volunteer Fire Service



### Base specification

- Chassis:
  - › Type: MB Sprinter 519 CDI
  - › Engine output: 114 kW (190 hp)
  - › Drive: Permanent all-wheel drive with off-road reduction
  - › Wheelbase: 3,665 mm
  - › Ladder holder for 2-part 10 m extension ladder
  - › Folding access ladder swivel-mounted
  - › COMFORT roof box with cover including lighting L = 2,000 mm, W = 430 mm, H = 300 mm
- Cabin:
  - › Crew: 1 + 8 (3 / 3 / 3)
  - › Three 3-point safety belts for driver and passenger
  - › Pivoting doors left and right
  - › Crew cabin: Fixed Rosenbauer crew cabin integrated in the vehicle interior
  - › Folding working table
  - › 2 x luggage nets in crew cabin
- Vehicle body:
  - › Panel van with Rosenbauer lightweight metal-roller shutters with barlocks left, right and on rear
  - › Interior made from aluminum profiles and aluminum sandwich technology vertical safety partition wall between crew cabin and equipment compartment
- Roof:
  - › Accessible GFK roof with integrated warning devices and anti-slip coating
- Equipment compartment:
  - › Rosenbauer COMFORT holder system
  - › Pullout platform as full platform for portable fire pump with extension length of up to 1,500 mm
  - › Holders for secure storage of equipment as well as ergonomic removal
  - › 2 COMFORT drawers in middle for various equipment
  - › Rotating shelf for secure storage of the generator
- Loading:
  - › KLF standard equipment in accordance with ÖBFV-RL FA-02
- Control system:
  - › Rosenbauer central electrical system with switch console for: rotating beacon, horn, flashing lights, surrounding area lighting, traffic control unit, etc.

## CL - Compact Line KLF, Small fire truck



- Additional equipment vehicle body
  - › Surrounding area lighting with 2 LED spotlights left and right on roller shutter cover and LED spotlight on rear, controlled from driver's cabin
  - › Battery-charge-retention device for vehicle battery, generator and portable fire pump
  - › 230 V input left front
  - › LED flashing lights blue front recessed in radiator grille
  - › Holder block for chainsaws incl pneumatic accessories Floodlight tower with 4 x 35 W LED floodlights incl. water protection boxes



### Dimensions and weight

L x W x H	approx. 6,100 x 2,420 x 2,780 mm
Permissible total weight:	5,300 kg



### Contact

Rosenbauer International AG  
Paschinger Strasse 90  
4060 Leonding, Austria  
Tel.: +43 732 6794-0  
Fax: +43 732 6794-91

[www.rosenbauer.com](http://www.rosenbauer.com)

[www.facebook.com/rosenbauergroup](https://www.facebook.com/rosenbauergroup)

Text and images non-binding. The images may depict special editions that are only available at an additional charge.  
Subject to change due to technical advances.

Vers. 1.0  
DoR\_6/17/2011