

Compact Line

MLF, medium sized pumper



pursuant to EN1846-2, DIN 14530-2 / Tiefenbach - Oberstdorf District Volunteer Fire Service



Basic specifications

- Chassis:
 - › Type: Iveco Daily 70C17 4x4
 - › Engine Output: 125 kW (170 hp) Euro 5
 - › Transmission: 6-gear gearbox
 - › Wheelbase: 3,750 mm
- Cab:
 - › Crew: 1 + 5 (2/2/2)
 - › Driver's cab: original Iveco cab, individual co-driver seat
 - › Rosenbauer crew cabin (long version), fully integrated into the large volume superstructure
 - › Two Rosenbauer COMFORT SCBA fixtures facing backwards
 - › Two Rosenbauer COMFORT SCBA fixtures with pneumatic locking, facing forwards
- Superstructure:
 - › Rosenbauer lightweight design large volume superstructure consisting of laser-cut aluminum components and aluminum sandwich sheets
 - › Especially low loading height, as the auxiliary frame is integrated into the floor sandwich
- Equipment compartments:
 - › Rosenbauer electrical superstructure locks and contoured shutters, which allow access to the entire equipment after single activation
- › Deep storage compartments both in front of and behind the rear axle
- › Variable interior space design according to fire service requirements by means of Rosenbauer pullout boxes
- › Fixtures system for various payload items such as a motor chainsaw, motor cutter, high-performance fan, etc.
- Roof:
 - › Entirely walkable, painted with an anti-slip coating
 - › Climbing ladder with large handgrips
 - › Roof lighting
 - › COMFORT roof box with lid for equipment storage
- Extinguishing systems:
 - › 1,000 l extinguishing water tank
 - › 100 l foaming component tank
 - › Rosenbauer (N10) centrifugal pump
 - › Normal pressure output of up to 1,000 l/min at 10 bar outlet pressure
 - › DIGIDOS pressurized foam proportioning system with variable rates from 0.1 to 6 %

Compact Line

MLF, medium sized pumper



- Control system:
 - › Rosenbauer LCS (Logic Control System) monitors based on modern CAN bus technology
- Power supply
 - › 230 V feed sockets
 - › Integrated 6.5 kVA generator with four 230 V sockets integrated into the superstructure
- Warning lights and lighting:
 - › Two flashing light arrays on the driver's cab roof
 - › One flashing light array at the rear
 - › Front LED flashing lights, countersunk into the radiator grille
 - › MARTIN fire service compressor horn
 - › Loudspeaker system with radio and two-way radio switching
 - › Surrounding area lighting in the lateral superstructure surrounds, integrated into the LED system
 - › Pneumatic lighting mast, 4 x 46 W, LED lights, max. extension height: 2,000 mm



Dimensions and weight:

L x W x H	6,500 x 2,250 x 3,000 mm
Permitted total weight	7,200 kg



Contact

Rosenbauer International AG
Paschinger Straße 90
4060 Leonding, Austria
Tel.: +43 732 6794-0
Fax: +43 732 6794-91

www.rosenbauer.com

www.facebook.com/rosenbauergroup

Text and photos non-binding. The photos may show optional extras only available at extra charge. The right to make changes in accordance with technical progress is retained.

Vers. 1.0
REhr_2012-10-03