

HEIGHT SAFETY

LINQ ESSENTIAL HARNESS H101

DESCRIPTION

LINQ Essential Harness

PART CODE

H101

FEATURES AND BENEFITS

- 1 Medically designed for maximum moment of impact safety
- 2 Harness Design minimises wearer injury during and after fall
- 3 Pebble-weave Webbing Design provides maximum grip precluding incidental buckle slippage
- 4 Integrated Webbing strap and hardware placement minimises impact injury
- 5 Combined belay loop sub pelvic strap positioning reduces risk of throat and facial injury
- 6 Retro-reflectivity built into webbing
- 7 High Tenacity Polyester Webbing for enhanced resistance to UV and common solvents (contact LINQ help line if in doubt)
- 8 160kg Wearer capacity (combined weight of wearer; clothes and tools) when used in conjunction with a LINQ Shock Absorbing Lanyard.
- 9 Articulated chest Strap and shoulder Adjustment points, designed for female users.



APPLICATIONS

Fall Arrest, Construction, Ladder, Scaffolding, Warehouse

PRODUCT DETAILS

- Large Dorsal Dee Ring
- Front Belay Loops
- 2bar 3bar connector buckle


Webbing Material	Polyester; 45mm; UV Resilient; Solvent Resistant*; Liqui-pel water guard option available
Buckle Material	Corrosion resistant electrophoresis; high tensile light weight alloy steel
Fall Arrest Hardware	Drop Forged corrosion resistant electrophoresis high strength alloy steel
Thread	Polyester; 9.81Newtons (10kg); Extension at break 19.5%
Stitch Pattern	THETA Pattern combines 313 stitches to exceed 28kN of strength. ASNZ compliant colour contrast
Plastic Material	UV stabilised high density polyethylene
Weight	1.1kg
Web Tenacity	Range- Min 28kN Max 30kN
Drop Forged Dee Rings	Alloy Steel (standard): 40kN; Aluminium or Stainless Steel (option): 22kN minimum
Buckle Strength	12 to 17kN model dependant; laser etch or hard marked on buckle
Standards Compliance	AS/NZS 1891.1; with "5 ticks" mark of Certification

Reading of LINQ instruction manual prior to use is mandatory
Description and specification subject to change without notice
* if in doubt please contact the LINQ helpline

STANDARDS

Certified & Approved to AS/NZS 1891.1 with "5 ticks" mark of Certification

We utilise a continual improvement regime product spec subject to change without notice.



Australian Standard
AS/NZS 1891.1:2007
Lic:21481
SAI Global