

## Addressable Detector Bases

### XP95/Discovery Detector Base

All detectors in the XP95 and Discovery range fit the Intelligent Mounting Base. The mounting base is a low insertion force base with stainless steel contacts for the detector terminals. XPERT cards are supplied with all bases.

- XPERT addressing
- One way fit of detector
- Locking feature to prevent unauthorised detector removal

#### Item Numbers

EN54	AS7240/AS1603	
45681-210AMP	201-0004	Detector Base with Xpert Card
45681-361APO	201-0093	Detector Base (Black)



XP95/Discovery Base

### Low Power Relay Base

The Intelligent Low Power Relay Base incorporates a low power relay to control field equipment.

- Provides a set of voltage free contacts controlled by the remote output of a detector
- Draws negligible current
- Capable of switching up to 30V at 1A

EN54	AS7240/AS1603	
45681-242APO	201-0014	Low Power Relay Base with Xpert Card



Low Power Relay Base

#### Specifications

Dimensions	
Detector Base	100mm Dia x 8mm H
Relay Base	100mm Dia x 24mm H
IP Rating	IP23D (indoor use)
Weight	55 g

For further information refer Product Guide MAN3037.



WORLD LEADER OF INNOVATIVE SOLUTIONS  
IN FIRE DETECTION AND ALARM SYSTEMS

