



HEIGHT SAFETY

LINQ ELITE ADJUSTABLE LANYARD

DESCRIPTION

2mtr Adjustable Lanyard - Single and Double Leg

PART CODE

WLA1 Single Leg (+hardware, see table below)

WLA2 Double Leg (+hardware, see table below)

FEATURES AND BENEFITS

- 1 An exclusive Extended Length Energy Absorber (ELEA) designed to protect a worker of up to 160kg including tools and equipment
- 2 Drop forged lanyard hardware
- 3 Stitching patterns are sewn by computer controlled bar tacking machinery for precision using UV resistant high tenacity polyester yarn with 100newton (10kg) breaking strength
- 4 Unique THETA stitch pattern has 423 stitches resulting in a strength that matches the lanyard's webbing strength.
- 5 Adjusts - 0.9m to 2m
- 6 Ideal for situations that require length adjustment.

PRODUCT DETAILS

- Australian designed, engineered, and MADE
- Webbing Tenacity= 33kN
- Webbing is UV rated to meet AS/NZS 1891.1 standard
- 'THETA' stitch pattern (equals 3300kg strength). Engineered to match webbing strength to ensure no weak point in the harness assembly.
- Contrast stitch thread colour for easy inspection
- Standard LINQ shock absorber is rated for wearer of up to 160kg. Including tooling and equipment
- Drop forged D Transition point doubles as a spare leg stowage point
- Adjusts - 0.9m to 2m

Webbing Material	Polyester; 45mm; UV Resilient; Solvent Resistant*
Fall Arrest Hardware	Drop Forged corrosion resistant electrophoresis high strength alloy steel
Stitch Pattern	THETA Pattern combines 423 stitches to exceed 33kN of strength. ASNZ compliant colour contrast
Web Tenacity	Range- Min 30kN Max 33kN
Standards Compliance	AS/NZS 1891.1; with "5 ticks" mark of Certification

Reading of LINQ instruction manual prior to use is mandatory
 Description and specification subject to change without notice
 * if in doubt please contact the LINQ helpline

STANDARDS

Certified & Approved to AS/NZS 1891.1 with "5 ticks" mark of Certification

We utilise a continual improvement regime product spec subject to change without notice.



HARDWARE AVAILABLE

Note: 1st hardware code listed is connected to the body.
e.g. **KDSN**. Double action karabiner to body and snap hook on lanyard end

Use Code

e.g. **WLA1KDSN** (Karabiner Double action/Snap Hook)
WLA2KDSN includes 1 x Karabiner Double Action & 2 x Snap Hook

KD	Karabiner Double Action Steel Alloy 19mm
KS	Karabiner Screw Gate Steel Alloy 18mm
KT	Karabiner Triple Action Steel Alloy 26mm
KTS	Karabiner Triple Action Stainless Steel 27mm
SD	Scaffold Hook Double Action Steel Alloy 68mm
ST	Triple Action Scaffold Hook Steel Alloy 68mm
GS	Giant Double Action Scaffold Hook Aluminium 110mm
SN	Snap Hook