

# PRODUCT SPECIFICATION.

## SOUTHERN CROSS SPIN-FX

312630 ▶

**Description:** 150mm high ankle boot with scalloped padded collar and tongue plus low profile scuff cap.

**Upper Materials:** Cowhide water-resistant Nubuck leather and stitched with Nylon thread.

**Toe Cap:** 200J Safety Steel.

**Lining Materials:** This boot is lined with Baltico® and SpacerMesh® which are soft, non-abrasive, hydrophobic material that wicks perspiration away from the foot, enabling the skin to remain cool and dry.

**SPIN-FX Powered by Boa® Closure System:** This boot is designed with a closure system reinventing how work boots perform. Simply turning the dial will give you a perfect, comfortable fit. A simple pull of the dial immediately loosens your boots to be relaxingly kicked off at the end of a long day. No more loose or straggling shoelaces. Improved ankle support provides secure foot comfort increasing work safety & efficiency.


**Full Innersole:** A full length footbed that is inserted into the footwear to offer additional support and comfort. This footbed is made from soft polyurethane that will retain its shape and thickness throughout the life of the boot.

**Insole:** Heavy-duty, flexible anti-bacterial non-woven insole.

**Midsole:** Directly moulded Polyurethane midsole for greater shock absorption.

**Outsole:** Antistatic Thermoplastic Urethane (TPU) outsole for superior wear properties. Heat resistant to 130°C.

**Trisole™ Comfort Technology Soling System:** The Steel Blue soling system is a patented three density soling system that offers a high level of comfort, shock absorbency and energy return. The system uses PORON® an shock absorbing insole under the foot to give the wearer superior comfort and offers similar shock absorbency and comfort to sports footwear.



**STEEL  
BLUE**  
100% COMFORT



### SOUTHERN CROSS (312630) FEATURES:



**ALL STEEL BLUE SOUTHERN CROSS BOOTS ARE INDEPENDENTLY CERTIFIED TO MAJOR INTERNATIONAL SAFETY STANDARDS.**

Meets International Safety Standards

- ✓ Australian/NZ Standard AS/NZS 2210.3
- ✓ American Standard ASTM F2413
- ✓ European Standard EN ISO20345

Endorsed by:



**SIZES:**

- 4 - 14
- 6.5 - 12.5 (half sizes available)